

MARIAFLORA


ITALIAN LUXURY PERFORMANCE FABRICS

Mariaflora fabrics pass NFPA260/UFAC class 1 and BULLETIN 117-2013.

Upon request, we are able to treat all fabrics to meet the requirements of NFPA701 and IMO FTPC P8.

In the United States, if Mariaflora fabrics are used for upholstery, they must be combined with a barrier material that meets the requirements of CPSC Upholstered Furniture Flammability Standard (TB 117-2013).

See all the certificates attached below:



DIVERSIFIED
TESTING LABORATORIES, INC.
WORLDWIDE SERVICE

“We Test Per Your Request”

336 WEST FRONT STREET
P.O. BOX 4004
BURLINGTON, NORTH CAROLINA 27215
PHONE (336) 227-7710 • FAX (336) 227-1175
www.diversifiedtestinglabs.com

March 2, 2020

FILIPPO UECHER SRL
Via Gramsci, 48
13875 – Ponderano – BI
ITALY

Reference: Laboratory Test Report
Lab Identification No. 40497
Invoice No. 71720

Dear FILIPPO UECHER SRL

One (1) fabric sample, identified **ARTICLE: MARIAFLORA 100% ACRYLIC SOLUTION DYED**, was received and tested in accordance with the NFPA 260, "Cigarette Ignition Resistance of Components of Upholstered Furniture, 2019 Edition", (Cover Fabric Test). The results are as follows:

Test Results

Vertical Char Lengths

10mm

12mm

10mm

The sample submitted **meets** the requirements of the above standard and may be considered a **Class I Cover Fabric**. There were no ignitions on any of the three specimens tested. In addition, none of the three test specimens displayed a vertical char which was equal to or greater than 45 mm.


If there are any questions or when we can be of further assistance, please let us know.

Sincerely,

Brian S. Dement

BSD/mr





DIVERSIFIED
TESTING LABORATORIES, INC.
WORLDWIDE SERVICE

"We Test Per Your Request"

336 WEST FRONT STREET
P.O. BOX 4004
BURLINGTON, NORTH CAROLINA 27215
PHONE (336) 227-7710 • FAX (336) 227-1175
www.diversifiedtestinglabs.com

September 28, 2021

FILIPPO UECHER SRL
Via Gramsci, 48
13875 – Ponderano – BI
ITALY

Reference: Laboratory Test Report
Lab Identification No. 47373
Invoice No. 78628

Dear FILIPPO UECHER SRL

One (1) sample, identified as **MARIAFLORA FABRIC**, was received and tested in accordance with the California Technical Bulletin 117-2013, Section 1, Cover Fabric Test. The results are as follows:

Test Results

Vertical Char Lengths

10mm

12mm

11mm

The sample submitted **meets** the requirements of the above standard. There were no ignitions or smoldering after 45 minutes on any of the three specimens tested. In addition, none of the three test specimens displayed a char which was greater than 45 mm.

If there are any questions or when we can be of further assistance, please let us know.

Sincerely,

Brian S. Dement

BSD/mr





For the Account of: Filippo Uecher Srl
Via Leonardo da Vinci N 5
Quarenga Biella
Italy 13854

Client's Identification: MariaFlora fabrics
Alta and Knit Backing

CERTIFICATE OF TESTING

TEST PERFORMED: NFPA 260 Standard Methods of Tests and Classification System for Cigarette Ignition Resistance of Components of Upholstered Furniture – 2013; Fabric Cover Test and UFAC Fabric Classification Test Method – 1990; Standard Test Methods for Cigarette Ignition Resistance of Components of Upholstered Furniture ASTM E 1353-16 – Cover Fabric Test

TEST RESULTS

Specimen	Char Length (in)
1	0.5
2	0.5
3	0.6

NOTES

Test Conditions: 70 ±4°F, 65 ±5% Relative Humidity

Dev-009: Used SRM 1196 Equivalent
Lot #

ACCEPTANCE CRITERIA

1. If the test specimen has no ignition, or if no individual specimen yields a vertical char of 45 mm (1.75 in.; ASTM states 1.8 in.) or less, the fabric is classified a Class I cover fabric.
2. If the vertical char of the test specimen greater than 45 mm (1.75 in.; ASTM states 1.8 in), the fabric is classified a Class II cover fabric.
3. If an obvious ignition of the polyurethane substrate occurs on the test assembly, the fabric is classified a Class II cover fabric.

CONCLUSION Based on the above Results and Acceptance Criteria, the item tested is:

- Class I
 Class II

CERTIFICATION I certify that the above results were obtained after testing specimen in accordance with the procedures and equipment specified by the standard stated above.

Authorized Signature

Date Order Completed: 07/21/2020